

Life Golf Car www.lifegolf.net

Specification Sheet

MODEL NO.:	DN-14C

GENERAL SPECIFICATION:

Battery	6V216AH*12 US batteries	
Motor	72V5KW	
Controller	AXE 400, Full electric speed Curtis controller , 72V400A	
Differential	Whole style steel rear axle, reduction ratio: 12.49	
Charger	Full automatic high frequency charger, 72V20A	
Suspension:	Macpheron strut suspension	1 1 3
Brakes	Four wheels hydraulic braking system and independent parking brake	
Passenger capacity	14	
Distance per charge (km)	70-80	
Max. speed (km/h)	28	
Charging time(h)	10-12h	
Minimum turning radius (m)	≤6.5	
Max. climbing ability (loaded)	20%	
Park ability (unloaded)	20%	
Slope starting ability	20%	
Brake range (m)	5	
Overall dimensions(mm)	4900*1550*2080	
Max. loading weight(kgs)	1200	
Front and rear axle loading(kgs)	600/700	
Net weight(kgs)	1300	
Chassis	Steel	
Wheel base(mm)	2700	
Wheel tread(front,mm)	1240	
Wheel tread(rear,mm)	1220	
Ground clearance(mm)	135	
Tires:	165/70R 13 79S	
Quantity per Container	2PCS /40HQ	

STANDARD CONFIGURATION:

DESCRPTIONS:	REMARKS	
Body	Fiber glass body	
Body Roof	Steel frame + fiber glass cover	
Windshield	One-piece see-through Acryl windshield	
Dashboard	White fiber glass, battery capacity indicator, turning and speed indicator	
Beverage holders	4 cups drink holders	

PAYMENT TERMS:

If FOB terms, T/T 30% deposit at order, T/T 70% to be paid before the delivery

If CFR or CIF terms, T/T 30% deposit at order, T/T 70% to be paid against the fax copy of Bill of lading.

LEAD TIME:

Around 4-5 Weeks after getting 30% deposit.